



PIERCAN USA INC.

Your critical link between product and personnel



Product sheet for Polyurethane/CSM Long Glove



GLOVE BOX / LONG GLOVES						
	PART NUMBER	PORT CUFF SIZE	DESCRIPTION	STANDARD LENGTH	HAND SIZES (new Universal size)	AMBI L/R
POLYURETHANE		US/FR	UY (~63% Polyurethane and ~37% CSM)			
	6 UY 1232-X	6"/150 mm	12 MIL or 0.3mm	32"/812mm	8.5, 9.75, 10.5	A or L/R
	6 UY 2032-X	6"/150mm	20 MIL or 0.5 mm		8.5, 9.75, 10.5	A or L/R
	7 UY 1232-X	6"/150 mm	12 MIL or 0.3mm		8.5, 9.75, 10.5, U	A or L/R
	7 UY 2032-X	7"/175mm	20 MIL or 0.5 mm		8.5, 9.75, 10.5, U	A or L/R
	7 UY 2032-Xv	7"/175mm	20 with velcro attachments		8.5, 9.75, 10.5, U	A or L/R
	8 UY 1232-X	8"/200mm	12 MIL or 0.3 mm		8.5, 9.75, 10.5, U	A or L/R
	8 UY 2032-X	8"/200mm	20 MIL or 0.5 mm		8.5, 9.75, 10.5, U	A or L/R
	8 UY 2032-Xv	8"/200mm	20 with velcro attachments		8.5, 9.75, 10.5, U	A or L/R
	8 UY 2030-Xv	8"/200mm	20 with velcro attachments	30"/750mm	8.5, 9.75, 10.5, U	A or L/R
	10 UY 1232-X	10"/250mm	12 MIL or 0.3 mm	32"/812mm	8.5, 9.75, 10.5	A
	10 UY 2032-X	10"/250mm	20 MIL or 0.5 mm		8.5, 9.75, 10.5	A
	12 UY 1232-X	10"/250mm	12 MIL or 0.3 mm		9.75	A
	12 UY 2032-X	12"/305mm	20 MIL or 0.5 mm		9.75	A

PIERCAN USA Inc.
 www.piercanusa.com
 160 Bosstick Blvd, San Marcos, CA 90269
 (760)599-4543
 Consult our YouTube channel : PIERCAN USA Inc
 INTL Transport schedule "B"/Tariff code 4002410000

High mechanical properties, puncture and tear resistance
Highest performance with in situ leak detectors
High resistance to UV Rays/Ozone
Natural aging
Very resistant to reducing acids, diluted acids, alkalis and salts
High temperature limit : 160F
Shelf life : 3 years

NAICS CODE : 339113